

The International Journal

# Racecar engineering

AOL Keyword: Racecar Engineering



## TUNING THE K-SERIES

How to extract reliable power from Rover's lightweight four



## DAMPER TEST EQUIPMENT

The latest in workshop-based shock absorber testing rigs


January 2005 • Vol 15 No 01

[www.racecar-engineering.com](http://www.racecar-engineering.com)

UK £4.50 • USA \$8.95

## BARRED

How front torque transfer works and why it had to go



## Brand new Formula Ford

A close look at the  
Spirit WL05

## How low can you go?

Weight distribution  
in a World Rally car



## Smooth underfloors

Removing some of the clutter from the underfloor area can have aerodynamic benefits

**W**e've been studying the effect of changes on a virtual model of a NASCAR racecar in recent issues, and seen that airdams, splitters and diffusers have all produced very useful and efficient benefits in terms of downforce gains for little, if any extra drag (and even reduced drag in some cases).

The model that Advantage CFD used for this work included some pretty realistic representations of exhaust pipes and some chassis members in order that the simulated underbody airflow was also reasonably realistic. With minor alterations to the CAD model it was possible to perform CFD runs with and without these underbody protuberances (see figures 1 and 2), thus simulating the tidying up of the underside as if the pipework had been tucked within the underside panelling instead of hanging below it. So, although this wasn't quite the same as installing a completely smooth panel, it did make it possible to see what a degree of 'smoothing' of the underbody could achieve.

The results were, perhaps, not exactly surprising, though the details make for illuminating study. Table 1 shows what happened to the downforce figures. As in previous articles, the simulated air velocity was 50m/s (180km/h or 112mph).

Table 1: downforce changes

	Rough floor, N	Smooth floor, N	$\Delta$ , N
Body	-1752 (lift)	-1682	70 (less lift)
Wheels	-183 (lift)	-190	7
Underfloor	3232 (downforce)	3262	30 (more downforce)
Rear spoiler	133	133	0
<b>TOTAL</b>	<b>1430</b>	<b>1523</b>	<b>93 (6.5 per cent more downforce)</b>

In short, there was a 6.5 per cent increase in downforce resulting from the smoother underside – a useful gain. Let's dwell on how that gain accrued.

Of the 93N benefit to overall downforce, the majority (70N) came from lift reduction over the upper surface of the car's body, on the face of it a surprising consequence of removing underbody clutter. But, as the result of removing the exposed pipes and chassis members, the airflow under

Figure 1: 3D NASCAR model with 'rough' underside



Figure 2: pipes and chassis tubes removed to smooth out underside



the car increased. This has led to a fairly uniform reduction in flow over the body, reducing the naturally occurring lift caused by that air accelerating over the body. Figure 3, a  $\Delta C_p Z$  plot showing the effect of the change to the model on the vertical component of the pressure coefficients, illustrates this.

To aid interpretation of these plots, blue/green shows an increase in local downforce, red/yellow shows a decrease in local downforce. Here then the colours show that there has been a reduction in lift over most of the body surface as the result of removing the underbody pipes and so forth. Although the actual pressure changes are very small (see the scale in figure 3), when integrated over the whole plan area they add up to the 70N lift reduction shown in table 1.

The story for the underside is more complex, and figure 4 is once more a  $\Delta C_p Z$  plot, this time showing the effect of the removal of the underside protuberances on the vertical component of the underside pressure coefficients. Generally the dominant blues and greens in the front half of the underside show that there has been a reduction in vertically →

Produced in association with Advantage CFD

**advantage** **CFD**

Tel: +44 (0)1280 846806

Email: [cfid@advantage-cfd.co.uk](mailto:cfid@advantage-cfd.co.uk)

Web site: [www.advantage-cfd.co.uk](http://www.advantage-cfd.co.uk)

Figure 3:  $\Delta C_{pZ}$  plot showing there has been a reduction in lift over most of the body surface as the result of removing the underbody pipes




Figure 4:  $\Delta C_{pZ}$  plot showing complex downforce changes in the underbody after removing the pipes




Figure 5:  $\Delta C_{pX}$  plot of the underside viewed from the rear shows that there is a reduction in X-direction pressure caused by removing the pipes





Figure 6:  $\Delta C_{pX}$  plot shows an increase in drag from the rear of the front and rear wheel cavities



acting static pressure in this area. This lower static pressure comes from two sources: the increased flow under the car and the reduction in total pressure arising from increased losses under the forward section.

But aft of the central crossbeam location, reds and yellows dominate, indicating that the pressure change here is upward acting, leading to downforce reduction in the rear underbody when the pipes and chassis members have been removed. This also seems curious but interestingly, when the chassis tubes are in place, the central crossbeam causes separation and hence substantial losses, leading to much reduced static pressure and hence more downforce in the rear underbody. Removing the crossbeam increases the flow, which also reduces the static pressure, but this effect is smaller than that caused by the losses from the crossbeam, so the overall effect, rather surprisingly, is a loss of downforce from the rear section when the crossbeam is removed.

## Complex changes

So the changes to downforce from the underside are complex and, although there is an overall gain here, it is smaller than might have been imagined. It also points to the fact that the overall downforce gain is forward biased. The changes to drag are small, but interesting in their detail too, once more alluding to the complexity of the airflow in such a situation. Table 2 summarises.

Overall, there is a very modest one per cent reduction in drag, smaller perhaps than might have been imagined but still, in combination with a downforce increase, something of a bonus.

It appears from table 2 that the biggest part of the drag reduction accrues from the wheels. Figure 5 helps to explain this. It is a  $\Delta C_{pX}$  plot, showing changes in the X-direction (rearward acting) component of the

Table 2: drag changes

	Rough floor, N	Smooth floor, N	$\Delta$ , N
Body	767	767	0
Wheels	247	235	-12
Underfloor	533	527	-6
Rear spoiler	271	271	0
<b>TOTAL</b>	<b>1818</b>	<b>1800</b>	<b>-18 (1 per cent less drag)</b>

pressure coefficients resulting from the removal of the pipes and tubes. Blue/green shows a decrease in local drag, red/yellow shows an increase in local drag. This view from the rear shows that there is a reduction in X-direction pressure caused by removing the pipes and tubes. This arises from the aforementioned increase in static pressure under the rear of the car acting on the rear faces of the tyres, which counteracts drag. But there is also an increase in drag from the rear of the front and rear wheel cavities – this the result of the increased flow colliding with these near vertical faces, as shown by the red colours in the  $\Delta C_{pX}$  plot in figure 6. Again, a complex picture that, in this instance, results in a small overall drag reduction.

It seems probable that a fully smooth underfloor would achieve a somewhat different result, but then the questions of rake angle and profile would come into play – these could be subjects for future Aerobytes. One thing is certain from this study however, where there are complex flows it is very unwise to make assumptions on likely results. **RE**

■ Next month we'll look at rear spoilers on our NASCAR model



# SUBSCRIBE TODAY

and stay one step ahead for 30% less!



THE INTERNATIONAL JOURNAL  
**Racecar**  
engineering

## • Save 30%

off the normal price

- ALL the latest industry insights before the competition!
- NEVER miss an issue
- NO price increases for 12 months
- FREE postage and packing
- GUARANTEED delivery to your door, worldwide
- FULL satisfaction guaranteed



For a rapid order call our hotline

**Tel: +44 (0)845 676 7778**

Please quote 26T. Lines open 7 days a week, 9.00am-9.00pm (UK time)  
OR SUBSCRIBE ONLINE AT [WWW.RACECAR-ENGINEERING.COM](http://WWW.RACECAR-ENGINEERING.COM)



Click here to download our **new** digital version now  
or go to [www.racecar-engineering.com/digital](http://www.racecar-engineering.com/digital)

## SUBSCRIPTION ORDER FORM

Simply complete this form, attach your payment and send it to:

UK: Racecar Engineering Subscriptions,  
**FREEPOST CY1061, Haywards Heath,  
West Sussex RH16 3ZA, UK** (NO STAMP REQUIRED)  
Overseas: Racecar Engineering Subscriptions,  
**PO Box 272, Haywards Heath,  
West Sussex RH16 3FS, UK** (PLEASE AFFIX CORRECT POSTAGE)

☒ Yes, I would like to subscribe to **Racecar Engineering**  
and get **30% off** the normal price

**12 issues Offer price**

<input type="checkbox"/> UK (annual)	£37.80	<b>SAVE 30%</b>
<input type="checkbox"/> UK (6 monthly direct debit)	£18.90	<b>SAVE 30%</b>
<input type="checkbox"/> USA	\$86.10	<b>SAVE 30%</b>
<input type="checkbox"/> Western Europe & Eire	€64.75	<b>SAVE 30%</b>
<input type="checkbox"/> Rest of World	£53.90	<b>SAVE 30%</b>

**N.B.** All overseas subscriptions receive an airmail service.  
All prices are discounted against our standard subscription rates.

### ATTENTION ALL NORTH AMERICAN SUBSCRIBERS

**TOLL FREE:** 1-800 EWA 4454  
**Fax:** 732 424 7814  
**Web address:** [www.ewacars.com](http://www.ewacars.com) **CLICK HERE**  
**Postal address:** EWA, 205 US Highway 22  
Green Brook, New Jersey, 08812 USA

### YOUR DETAILS

Title: .....Initial: .....Surname: .....

Address: .....

Postcode: .....Country: .....

Evening Tel: .....

If you would like to receive emails from Racecar Engineering and IPC containing news, special offers and products and service information, and take part in our magazine research via email, please include your email address below:

Email: .....

### PAYMENT DETAILS

☐ I enclose a cheque for £/\$/€ .....  
made payable to IPC MEDIA LTD.

☐ I wish to pay by    Mastercard ☐    Visa ☐    Amex ☐  
                                 Diners ☐    Delta ☐

□ □ □ □    □ □ □ □    □ □ □ □    □ □ □ □

Expiry Date: .....Signature .....Date .....

**Data protection:** Racecar Engineering, published by IPC Media Ltd (IPC), will collect your personal information to process your order. Racecar Engineering and IPC would like to contact you by post or telephone to promote and ask your opinion on our magazines and services. Please tick here if you prefer **not** to hear from us ☐. IPC may occasionally pass your details to carefully selected organisations so they can contact you by telephone or post with regards to promoting and researching their products and services. Please tick here if you prefer **not** to be contacted ☐.

Offer Closing Date: 31 December 2005 (26T)