

The International Journal

# Racecar engineering

AOL Keyword: Racecar Engineering



**2.0L ROVER  
K SERIES**  
Tuneable four stretched  
to the limit for WSR's  
touring car challengers



**DIFFERENTIAL  
PROGRESS**  
Latest developments in  
final drives and torque  
split control systems

August 2004 • Vol 14 No 8

www.racecar-engineering.com

UK £4.50 • USA \$8.95

## Cross culture

**Champion technology behind the  
European Rallycross Xsara**



### Behind the scenes at Le Mans 2004

Technology report from  
the 24-hour classic

### Understanding trail braking

An engineer's guide to a much  
misunderstood driving technique

### Racing an LMP1

Running the first car built  
to the new sportscar rules





## Wing camber

Continuing our look at fundamental wing parameters, Advantage CFD helps us investigate the effects of changing wing camber

Last month we saw that in situations that mandate a single wing element, and also the maximum dimensions of that wing element, the only way to extract more downforce from the wing is to manipulate its lift coefficient, as stated by the equation:

$$\text{Lift (downforce)} = \rho \times p \times A \times C_L \times v^2$$

where  $\rho$ , the Greek letter rho, is air density,  $A$  is wing plan area and  $v$  is air velocity. Changing the wing's thickness is one way to do that, as we saw in the last issue, while changing its camber (the amount of front to rear curvature in the profile – see figure 1) is another, though caution should be exercised to ensure you don't go outside any relevant dimensions specified in the regulations.

The textbooks are a lot clearer on the effects of altering wing camber than they are on changing thickness. The indications are that more camber gives more lift (downforce in our context) at a given angle, although the suggestion is that stall may occur at lower angles. It isn't clear from the texts whether maximum downforce should be expected to change with camber.

So, how much camber is good? What happens to the airflow around a wing as camber is increased? Advantage CFD set up a range of wing models once again using the NACA 63<sub>2</sub>-615 profile as a start point. They then manipulated this shape to put more or less camber into it, maintaining the location of maximum camber at the same position along




Figure 1: wing terminology

Produced in association with Advantage CFD.

**advantage** 

Tel: +44 (0)1280 846806

Email: [cfid@advantage-cfd.co.uk](mailto:cfid@advantage-cfd.co.uk)

Web site: [www.advantage-cfd.co.uk](http://www.advantage-cfd.co.uk)



More camber equals more downforce, but what is the corresponding effect on efficiency?

the wing chord in all cases. And then a set of two-dimensional CFD runs at a virtual air speed of 50m/s (180km/h or 112mph) were performed at a range of angles of attack, and over a range of cambers from four to 12 per cent. Camber value is expressed as a percentage of the chord dimension.

### Peak downforce

Downforce versus angle of attack for the range of cambers studied is plotted in figure 2. (Note: missing points indicate that unsteady flow conditions in the more extreme cases prevented solutions being calculated). The first noticeable relationship is that, for a given angle of attack, downforce does increase with greater camber, at least up to camber values of nine per cent applied to this particular 'family' of wing profiles. Secondly, peak downforce also increases with camber, again up to the nine per cent camber value at least. Thus, the whole downforce curve is translated vertically as camber is incrementally increased. And the stall angle appears to be the same, 14 degrees, in each case, again up to nine per cent camber.

However, the highest camber value studied here does behave differently. While it follows the same slope up to an angle of attack of eight degrees, performance tails off sooner than with the lower camber wings. The 12 per cent camber wing peaks at just 12 degrees, with a lower downforce value than that achieved by the nine per cent camber wing at this angle. The obvious conclusion is that the geometry generated by giving this wing profile 12 per cent camber is pushing things too far, and nine per cent camber looks to be optimum here for maximum downforce.

Figures 3, 4 and 5 show pressure-coloured flow patterns from three of the runs performed, all of these being at 8 degrees, but at cambers of six, nine and 12 per cent. Evident features include the generation of an increasingly large low-pressure region below the lower surface as camber is increased. And the flow around the wings changes as camber is increased, too, with almost fully attached flow on the underside of the lowest camber wing here, flow separation developing at nine per cent camber, while substantial separation has developed at 12 per cent. ➔






Figure 2: downforce versus angle of attack for a range of cambers




Figure 3: pressure-coloured streamlines at six per cent camber, eight degrees angle of attack – flow almost fully attached to the lower surface




Figure 4: pressure-coloured streamlines at nine per cent camber, eight degrees angle of attack – flow separation beginning to develop

Thus, although downforce increases with each additional increment of camber, it is clear that the airflow is struggling to remain attached to the wing as higher values of camber are applied.

Figure 6 shows an extreme case, where the 12 per cent camber wing at 12 degrees angle of attack is showing extensive flow separation, so that even the large increase in angle of attack over figure 5 has produced only a minor increase in downforce. The high pressure developed on the upper surface of the wing may be considerable, but the flow on the lower surface has all but broken down.

So, to get more downforce from a single element wing, add more camber, but only up to a point. The optimum value found here should not be taken as a definite figure though, rather as just an indicator that there will be a maximum camber value that any particular wing profile can be 'morphed' to.

## Peak efficiency

But, as is well known, maximising downforce is often only part of the story. As discussed in the last column, drag is generally a factor, too. As this was a 2D CFD study, 3D drag effects like the vortex formation created by the generation of downforce by a finite span wing were not evaluated.




Figure 5: pressure-coloured streamlines at 12 per cent camber, eight degrees angle of attack – substantial flow separation




Figure 6: pressure-coloured streamlines at 12 per cent camber, 12 degrees angle of attack – downforce gains have ceased




Figure 7: lift to drag ratio versus angle of attack for various cambers

But the profile drag (the sum of viscous drag and pressure drag) can be calculated using 2D techniques, and profile drag, like induced drag, does change with angle of attack. So we can get an idea of how profile drag alters with changes to camber. Figure 7 plots lift divided by drag, a measure of the wing's 2D efficiency, against angle of attack.

Again, the most obvious, and least surprising relationship shown here is that efficiency decreases as more downforce is generated, in a diminishing returns relationship with increasing angle of attack. Put another way, the best efficiency figures occur at lower camber values, although interestingly the six per cent camber profile is the most efficient shape up to eight degrees angle of attack, and only slightly less efficient than the four per cent camber wing at steeper angles.

Also, and importantly if one was searching for maximum downforce, it appears that additional camber increments at high angles of attack (and vice versa) produce proportionately smaller efficiency penalties. This might be relevant for those 'don't worry about the drag' situations where maximum speeds are not high and the corners demand as much downforce as possible.

● Next month we'll look at two-element wings.

RE

# SUBSCRIBE TODAY

and stay one step ahead for 30% less!



THE INTERNATIONAL JOURNAL  
**Racecar**  
engineering

## • Save 30%

off the normal price

- ALL the latest industry insights before the competition!
- NEVER miss an issue
- NO price increases for 12 months
- FREE postage and packing
- GUARANTEED delivery to your door, worldwide
- FULL satisfaction guaranteed



For a rapid order call our hotline

**Tel: +44 (0)845 676 7778**

Please quote 26T. Lines open 7 days a week, 9.00am-9.00pm (UK time)  
OR SUBSCRIBE ONLINE AT [WWW.RACECAR-ENGINEERING.COM](http://WWW.RACECAR-ENGINEERING.COM)



Click here to download our new digital version now  
or go to [www.racecar-engineering.com/digital](http://www.racecar-engineering.com/digital)

## SUBSCRIPTION ORDER FORM

Simply complete this form, attach your payment and send it to:

UK: Racecar Engineering Subscriptions,  
**FREEPOST CY1061, Haywards Heath,  
West Sussex RH16 3ZA, UK** (NO STAMP REQUIRED)  
Overseas: Racecar Engineering Subscriptions,  
**PO Box 272, Haywards Heath,  
West Sussex RH16 3FS, UK** (PLEASE AFFIX CORRECT POSTAGE)

☒ Yes, I would like to subscribe to **Racecar Engineering**  
and get **30% off** the normal price

**12 issues Offer price**

<input type="checkbox"/> UK (annual)	£37.80	<b>SAVE 30%</b>
<input type="checkbox"/> UK (6 monthly direct debit)	£18.90	<b>SAVE 30%</b>
<input type="checkbox"/> USA	\$86.10	<b>SAVE 30%</b>
<input type="checkbox"/> Western Europe & Eire	€64.75	<b>SAVE 30%</b>
<input type="checkbox"/> Rest of World	£53.90	<b>SAVE 30%</b>

**N.B.** All overseas subscriptions receive an airmail service.  
All prices are discounted against our standard subscription rates.

### ATTENTION ALL NORTH AMERICAN SUBSCRIBERS

**TOLL FREE:** 1-800 EWA 4454  
**Fax:** 732 424 7814  
**Web address:** [www.ewacars.com](http://www.ewacars.com) **CLICK HERE**  
**Postal address:** EWA, 205 US Highway 22  
Green Brook, New Jersey, 08812 USA

### YOUR DETAILS

Title: .....Initial: .....Surname: .....

Address: .....

Postcode: .....Country: .....

Evening Tel: .....

If you would like to receive emails from Racecar Engineering and IPC containing news, special offers and products and service information, and take part in our magazine research via email, please include your email address below:

Email: .....

### PAYMENT DETAILS

☐ I enclose a cheque for £/\$/€ .....  
made payable to IPC MEDIA LTD.

☐ I wish to pay by    Mastercard ☐    Visa ☐    Amex ☐  
                                 Diners ☐    Delta ☐

□ □ □ □    □ □ □ □    □ □ □ □    □ □ □ □

Expiry Date: .....Signature .....Date .....

**Data protection:** Racecar Engineering, published by IPC Media Ltd (IPC), will collect your personal information to process your order. Racecar Engineering and IPC would like to contact you by post or telephone to promote and ask your opinion on our magazines and services. Please tick here if you prefer **not** to hear from us ☐. IPC may occasionally pass your details to carefully selected organisations so they can contact you by telephone or post with regards to promoting and researching their products and services. Please tick here if you prefer **not** to be contacted ☐.

Offer Closing Date: 31 December 2005 (26T)