

The International Journal

Racecar engineering

AOL Keyword: Racecar Engineering



CAD AND THE REAL WORLD

How top-level computer-aided-design can work for practical constructors



REINVENTING THE RACE KART

The revolutionary new design that could turn kart racing on its head

May 2004 • Vol 14 No 5

www.racecar-engineering.com

UK £4.50 • USA \$8.95

Fastback

**Peugeot 307 CC: changing
the shape of world rallying**

Showing restraint


How HANS is dealing with
stiff opposition

Driven to win

Engineers talk about
working with drivers

Science friction

Brake pad
materials





Underbody downforce

Ground clearance and downforce



It is well known that ground clearance, along with the shape of the underbody, is one of the principal factors that influences the generation of underbody downforce on a racecar. As we've shown earlier in this series, given some freedom to shape the underbody, even if that is limited to running a diffuser at the rear of an otherwise flat underside (the venturi throat) – perhaps with nothing more than a moderate radius to the inlet – then the mechanism by which that downforce is created is in essence, that of a venturi tube.

The principle by which air is accelerated beneath the car, so reducing the pressure there as described in Bernoulli's theorem, is that of Conservation of Mass. This states that the mass flow through the venturi must be the same along its length. Hence, where the cross sectional area of the venturi reduces, the flow velocity increases in direct inverse proportion. And as Bernoulli tells us, increases in velocity lead to decreases in local pressure.

Continuing our examinations of underbody airflow, Advantage CFD ran some trials using two mathematical models, each based on a simplified 2m (6.5ft) long racecar sidepod. One set of calculations predicted downforce values at varying ground clearances based on Bernoulli's equation, while another did the same using 2D viscous computational fluid dynamics (CFD) methods on an essentially very similar model. The differences in the predictions were illuminating, as




Figure 1: downforce values at different ground clearances by Bernoulli and viscous CFD

was the detail produced in the CFD runs.

Air is accelerated into the throat of a venturi by being channelled into a reducing cross sectional area. The 'area ratio', that is, the ratio of the inlet area to the throat area, tells us by how much the velocity will increase, since velocity varies inversely with the area. Clearly the cross sectional area of the throat of a profiled underbody close to the ground depends very much on ground clearance, and the area ratio will increase more rapidly with ever-decreasing ground clearance. Thus, using Bernoulli-based calculations we might expect to see downforce predicted to rise rapidly with decreasing ground clearance, and the relevant line in the graph in figure 1 confirms this, with a classic inverse relationship curve.

The results predicted by viscous CFD are also plotted on this graph, and the picture is obviously very different in this case, most significantly at the smaller ground clearances. At the larger ground clearance end of the scale, where the volume of air affected by the viscous effects of

Produced in association with Advantage CFD.

advantageCFD

Tel: +44 (0)1280 846806

Email: cfd@advantage-cfd.co.uk

Web site: www.advantage-cfd.co.uk




Figure 2: pressure coefficient magnitudes and distribution plot at 20mm, 40mm and 100mm




Figure 3: flow separation is clearly a problem in the diffuser at 20mm ground clearance

the underbody surfaces is small relative to the overall airflow, the Bernoulli predictions and CFD predictions are actually very close. However, at ground clearances of around 70mm (2.7in) or less, the viscous effects are becoming ever more significant. By 20mm (0.79in) the air is being asked to flow through such a small gap that the viscous effects are dominant, reducing the downforce predicted by Bernoulli by about 80 per cent, and the downforce attains its maximum at 40mm (1.6in) ground clearance with this model. As a brief aside, the reason that the viscous CFD downforce value is slightly higher than the Bernoulli value at the 100mm (3.9in) ground clearance is because of necessary slight variations in the models, which meant that the effective inlet size was slightly bigger in the CFD model. Elsewhere, viscous effects masked this difference.

Figure 2 shows plots of pressure coefficients at three of the ground clearances tested using viscous CFD (the black silhouettes show the sidepod profile used here, which had inlet and diffuser angles fixed respectively at 10 degrees and 5 degrees). Looking first at the 100mm (3.9in) case, the pressure plot shows an evenly distributed, moderately low pressure along the venturi throat (flat section). At 40mm (1.6in) ground clearance significantly lower pressure is attained in the throat, and this gap achieves the highest overall downforce figure. Interestingly, in the case of the 20mm (0.79in) ground clearance model the inlet region actually sees positive pressure (and commensurate lift) before the flow steadily accelerates through the throat, attaining similarly low pressure to the 40mm (1.6in) case only at the rear of the throat. It appears that what might be called the 'viscous blockage' at this low ground clearance makes its effect felt right at the start of this downforce inducing device at 20mm (0.79in) gap.




Figure 4: at 40mm ground clearance, flow separation in the diffuser is greatly reduced




Figure 5: by 60mm ground clearance, separation in the diffuser has vanished altogether

There is also another interesting effect of reducing ground clearance. Just as the area ratio becomes more extreme at the inlet, so it does at the diffuser end of the venturi. Here the airflow is being asked to expand increasingly rapidly through the diffuser at smaller ground clearances. As the diffuser is a region of adverse pressure gradient anyway (the flow is trying to go from a low to a high pressure region, which it is only happy to do if asked nicely) the consequence of working the airflow too hard is that flow separation occurs. This can be seen in the velocity streamline diagram in figure 3, where at 20mm (0.79in) ground clearance flow separation in a distinct re-circulation region can be seen adjacent to the diffuser roof. Taking all these effects into account, the result at 20mm (0.79in) ground clearance is a downforce figure some 18.5 per cent lower than that achieved at 40mm (1.6in). Figure 4 shows the flow separation to be much smaller, and the general airflow velocity to be much higher at 40mm (1.6in), while at 60mm (2.36in) (figure 5) there is no separation apparent.

Conclusion

While initially a decreasing ground clearance does produce the expected increase in underbody downforce, it is clear that too small a gap leads to a reduction in downforce because of viscous effects. The general aim would appear to be to run the smallest ground clearance possible that maintains 'unblocked' flow and no diffuser separation. In the case of our sidepod model here, optimum downforce occurred at 40mm (1.6in) ground clearance, but fully attached flow with only a 4.3 per cent loss of downforce occurred at 60mm (2.36in), which might suggest a suitable operating range – for this model at least.

Next month: basic parameters that determine wing performance.



SUBSCRIBE TODAY

and stay one step ahead for 30% less!



THE INTERNATIONAL JOURNAL
Racecar
engineering

- **Save 30%** off the normal price
- **ALL** the latest industry insights before the competition!
- **NEVER** miss an issue
- **NO** price increases for 12 months
- **FREE** postage and packing
- **GUARANTEED** delivery to your door, worldwide
- **FULL** satisfaction guaranteed



For a rapid order call our hotline

Tel: +44 (0)845 676 7778

Please quote 26T. Lines open 7 days a week, 9.00am-9.00pm (UK time)
OR SUBSCRIBE ONLINE AT WWW.RACECAR-ENGINEERING.COM



Click here to download our **new** digital version now
or go to www.racecar-engineering.com/digital

SUBSCRIPTION ORDER FORM

Simply complete this form, attach your payment and send it to:

UK: Racecar Engineering Subscriptions,
**FREEPOST CY1061, Haywards Heath,
West Sussex RH16 3ZA, UK** (NO STAMP REQUIRED)
Overseas: Racecar Engineering Subscriptions,
**PO Box 272, Haywards Heath,
West Sussex RH16 3FS, UK** (PLEASE AFFIX CORRECT POSTAGE)

☒ Yes, I would like to subscribe to **Racecar Engineering**
and get **30% off** the normal price

12 issues Offer price

<input type="checkbox"/> UK (annual)	£37.80	SAVE 30%
<input type="checkbox"/> UK (6 monthly direct debit)	£18.90	SAVE 30%
<input type="checkbox"/> USA	\$86.10	SAVE 30%
<input type="checkbox"/> Western Europe & Eire	€64.75	SAVE 30%
<input type="checkbox"/> Rest of World	£53.90	SAVE 30%

N.B. All overseas subscriptions receive an airmail service.
All prices are discounted against our standard subscription rates.

ATTENTION ALL NORTH AMERICAN SUBSCRIBERS

TOLL FREE: 1-800 EWA 4454
Fax: 732 424 7814
Web address: www.ewacars.com **CLICK HERE**
Postal address: EWA, 205 US Highway 22
Green Brook, New Jersey, 08812 USA

YOUR DETAILS

Title:Initial:Surname:

Address:

Postcode:Country:

Evening Tel:

If you would like to receive emails from Racecar Engineering and IPC containing news, special offers and products and service information, and take part in our magazine research via email, please include your email address below:

Email:

PAYMENT DETAILS

☐ I enclose a cheque for £/\$/€
made payable to IPC MEDIA LTD.

☐ I wish to pay by Mastercard ☐ Visa ☐ Amex ☐
 Diners ☐ Delta ☐

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

Expiry Date:SignatureDate

Data protection: Racecar Engineering, published by IPC Media Ltd (IPC), will collect your personal information to process your order. Racecar Engineering and IPC would like to contact you by post or telephone to promote and ask your opinion on our magazines and services. Please tick here if you prefer **not** to hear from us ☐. IPC may occasionally pass your details to carefully selected organisations so they can contact you by telephone or post with regards to promoting and researching their products and services. Please tick here if you prefer **not** to be contacted ☐.

Offer Closing Date: 31 December 2005 (26T)